

MaxiSyn ISO 460

SDS Number: 10314 Revision Date: 2/4/2015

Page 1 of

1. Product and Company Identification

Manufacturer

Bade Incorporated 48 Sulfer Springs Road Irwin, PA 15642

Phone: 1-888-783-0363

Product Name: MaxiSyn ISO 460

Revision Date: 2/4/2015 SDS Number: 10314 CAS Number: Blend Product Code: 10314

Synonyms: Synthetic bearing and gear oil

For emergencies contact Chemtrec at 1-800-424-9300.

2. Hazards Identification

GHS Signal Word:

WARNING

GHS Classifications:

Health, Serious Eye Damage/Eye Irritation, 2 B

GHS Phrases:

H320-Causes eye irritation

GHS Precautionary Statements:

P305+351+338 - IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.



MaxiSyn ISO 460

SDS Number: 10314 Revision Date: 2/24/20

Page 2 of

3. Composition/Information on Ingredients

Ingredients:

Chemical Name	Percentage	CAS#
Synthetic base oils	90 - 95	Proprietary
Additives	5 - 10	Proprietary

4. First Aid Measures

Inhalation: If symptoms develop, move victim to fresh air.

If symptoms persist, obtain medical attention.

Skin Contact: Wash with soap and water.

Remove contaminated clothing and wash before reuse.

Get medical attention if needed.

Eye Contact: Flush with water for several minutes.

If effects occur, consult a physician.

Ingestion: Rinse mouth with water.

If symptoms develop, obtain medical attention.

5. Fire Fighting Measures

Flash Point: 176.7 C (350.1 F)

Flash Point Method: PMCC

Use dry powder, foam, or carbon dioxide fire extinguishers.

Water may be ineffective in fighting an oil fire unless used by experienced fire fighters.

6. Accidental Release Measures

Contain spilled material.

Collect insuitable and properly labeled containers. Pick up excess with inert absorbent material

Keep away from drains and ground water.



MaxiSyn ISO 460

SDS Number: 10314 Revision Date: 2/4/201

Page 3 of

7. Handling and Storage

Handling Precautions: Avoid contact with eyes, skin, or clothing.

Keep away from sources of ignition.

Handle with care and avoid spillage on the floor (slippage).

Storage Requirements: Keep away from sources of ignition.

8. Exposure Controls/Personal Protection

Engineering Controls: All ventilation should be designed in accordance with OSHA Standard (29 CFR 1910.94)

Solubility:

Nil in water

Personal Protective Equip: Use of safety glasses and gloves are recommended.

9. Physical and Chemical Properties

Appearance: Orange/

Yellow

Physical State: Liquid

Viscosity: 460 cST at 40 degrees C

10. Stability and Reactivity

Stability: Product is stable under normal conditions.

Conditions to Avoid: High temperatures and open flame.

11. Toxicological Information

Repeated skin contact with this product may cause dermatitis or an oil acne.

No test data available on product.

No component is listed as a carcinogen, mutagen, or teratogen.

LD50 / LC50 - No data available

12. Ecological Information

Avoid exposing to the environment, no specific aquatic data available.

13. Disposal Considerations

Dispose of in accordance with local regulations.

Do not flush to surface water or drains



MaxiSyn ISO 460

SDS Number: 10314 Revision Date: 2/4/201

Page 4

14. Transport Information

Not regulated by DOT.

15. Regulatory Information

This material or all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Ac (TSCA).

16. Other Information

The information contained in this Safety Data Sheet relates only to the specific material designated. Bade Incorporated assumes no legal responsibility for use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Bade Incorporated.