Safety Data Sheet (SDS)



Moly Maxi 6000 ISO 220

SDS Number: 11092 Revision Date: 1/19/201

Page 1 of

Section 1: Product and Company Identification

Manufacturer

Bade Incorporated 48 Sulfer Spring Road Irwin, PA 15642

Phone: 1-888-783-0363

Product Name: Moly Maxi 6000 ISO 220

Revision Date: 1/19/2015 SDS Number: 11092

Common Name: Hydrotreated heavy paraffinic oil

CAS Number: Blend Product Code: 11092

Synonyms: Zinc Free Antiwear Hydraulic Fluid

For emergencies contact Chemtrec at 1-800-424-9300.

2. Hazard Identification

GHS Signal Word: NONE

GHS Classifications: None, None, None

GHS Phrases: H000 - None

3. Composition/Information on Ingredients

Ingredients:

Chemical Name	Percentage	CASE #
Petroleum, solvent dewaxed heavy paraffinic oil	> 98	64742-65-0
Additives	< 3	Proprietary

Safety Data Sheet



Moly Maxi 6000 ISO 220

SDS Number: 11092 Revision Date: 1/19/201

Page 2 of

4. First Aid Measures

Inhalation: If symptoms develop, move victim to fresh air.

If symptoms persist, obtain medical attention.

Skin Contact: Wash with soap and water.

Remove contaminated clothing and wash before reuse. Get

medical attention if needed.

Eye Contact: Flush with water for several minutes.

If effects occur, consult a physician.

Ingestion: Rinse mouth with water.

If symptoms develop, obtain medical attention.

5. Fire Fighting Measures

Flash Point: 248.9 C (480.0 F)

Flash Point COC

Method:

Use dry powder, foam, or carbon dioxide fire extinguishers.

Water may be ineffective in fighting an oil fire unless used by experienced fire fighters.

6. Accidental Release Measures

Contain spilled material.

Collect insuitable and properly labeled containers.

Pickup excess with inertabsorbent material.

Keep away from drains and ground water.

7. Handling and Storage

Handling Precautions: Avoid contact with eyes, skin, or clothing.

Keep away from sources of ignition.

Handle with care and avoid spillage on the floor (slippage).

Storage Requirements: Keep away from sources of ignition.



Safety Data Sheet (SDS)

Moly Maxi 6000 ISO 220

SDS Number: 11092 Revision Date: 1/19/20

Page 3

8. Exposure Controls/Personal Protection

Engineering Controls: All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

Personal Protection Equip: Use of safety glasses and gloves are recommended.

9. Physical and Chemical Properties

Appearance: Amber

Physical State: Liquid Solubility: Nilinwater

Viscosity: 220 cSt at 40 degrees C Percent Volatile: Nil

Boiling Point: > 425 F

10. Stability and Reactivity

Stability: Product is stable under normal conditions. Conditions to Avoid: High temperatures and open flame.

11. Toxicological Information

Repeated skin contact with this product may cause dermatitis or an oil acne.

No test data available on product.

No component is listed as a carcinogen, mutagen, or teratogen.

LD50 / LC50 - No data available

12. Ecological Information

Avoid exposing to the environment, no specific aquatic data available

13. Disposal Considerations

Dispose of in accordance with local regulations.

Do not flush to surface water or drains.

14. Transport Information

Not regulated by DOT.

Safety Data Sheet (SDS)



Moly Maxi 6000 ISO 220

SDS Number: 11092 Revision Date: 1/19/20

Page 4

15. Regulatory Information

This material or all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act (TSCA).

16. Other Information

The information contained in this Safety Data Sheet relates only to the specific material designated. Bade Incorporated assumes no legal responsibility for use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Bade Incorporated.